



SEAL DOOR TO FLOOR
CONSTRUCTION PER
MANUFACTURER'S
INSTALLATION
INSTRUCTIONS.

2" FOAM INSULATION

8" CMU CORE FILLED

WINDOW & DOOR FLASHING
TAPE. CLEAN FLOOR AREA &
APPLY OVER ROUGH OPENING
FLOOR SURFACE EXTENDING 6"
UP EACH JAMB & OVERLAP
ONTO THRU-WALL FLASHING.

4" CONCRETE
SLAB

VERTICLE REBAR
AS REQUIRED BY
CODE

ANCHOR DOOR SILL TO
FLOOR CONSTRUCTION
PER MANUFACTURE'S
INSTALLATION
INSTRUCTIONS.



STRONGHOLD
INSULATED CONCRETE FORMS

BUILD TRUST

WWW.STRONGHOLDICF.COM

THESE TABLES AND DRAWINGS ARE PROVIDED AS A REFERENCE GUIDE FOR USE BY DESIGNERS. THE USE IS RESPONSIBLE FOR MODIFYING THE DRAWING AND INFORMATION AS NEEDED TO MEET APPLICABLE BUILDING CODE AND CONSTRUCTION PRACTICES. STRONGHOLD RESERVES THE RIGHT TO MAKE CHANGES TO THE DRAWINGS WITHOUT NOTICE AND ASSUMES NO LIABILITY IN CONNECTION WITH THE USE OF THIS DRAWING INCLUDING MODIFICATIONS, COPYING OR DISTRIBUTION.

DRAWN:

NILLES C.

DATE:

7.30.2024

DRAWING TYPE:

TITLE:

DOOR SILL DETAIL